



主要技术参数、性能
The Main Thchnology Performance

电路图 CTRCUTT	COM-NC -NO
额定值 RATINGS	5A 125VAC/250VAC
绝缘电阻 INSULATION STRENGTH	≥100MΩ
接触电阻 CONTACT RESISTANCCE	≤50MΩ
耐电压 TEST VOLTAGE	≥1000V AC/5S
电器寿命 ELECTONCAL LIFE	≥10, 000Cycles
温度等级 TEMPERATRE	10T85
操作力 (OF) OPERATING FORCE	≤0.15N
动作位置 (OP) OPERATING POSTTON	8.7±0.5mm

1	手柄 Moving arm	1	Stainless steel 不锈钢	
2	弹片 Spring sheet		QSn6.5-0.1 δ 0.1 磷青铜	
3	跳板 Moving piece	1	Brass H62 δ 0.4 黄铜	Ag Plating 镀银
4	动触点 Contact	1	Brass H62 黄铜	Ag Plating 镀银
5	长端子 Terminal	1	Brass H62 δ 0.5 黄铜	Ag Plating 镀银
6	短端子 Terminal	1	Brass H6.2 δ 0.5 黄铜	
7	三曲弯 Support	1	Brass H6.2 δ 0.5 黄铜	
8	基盖 Cover	1	PBT 420SEO(黑色)	
9	底座 Cover	1	PBT 420SEO(黑色)	
10	按钮 Plunger	1	PBT 420SEO(黑色)	

未注 公差 尺寸	线性	>0~6	±0.05
		>6~20	±0.1
		>20~50	±0.2
		>50~100	±0.4
		>100	±0.8
	角度尺寸		±2°
设计			
审核			
批准			
生效时间			

名称 Name	型号: KW4-Z4F		
	料号:		
设计 Micro Switch	模具 编号	单位: mm	比例:
		版本: B	视角:
	第 1 页 共 1 页		
乐清市戴尔电子有限公司 YUEQING DATER ELECTRON CO.,LTD			