

MG200 Series

Brushless Magnetic Driving Gear Pump

MG200XK Series Pump With Inside Controller



Typical Applications

- Food equipment: Automatic filling machine, coffee machine, food processing
- Medical equipment: hemodialysis machine, surgical instrument, skin care, disinfection and sterilization equipment, beauty equipment
- Printing equipment: ceramic inkjet printers, inkjet printer, photo machines, barcode machines
- Commercial equipment: laser cooling units, spray equipment, water treatment, welding & cutting, lab instrumentation

Strength

- 316L SS shell, PEEK gear, PTFE sealing, corrosion resistance, high temperature resistance, durable
- Driven by magnetic coupling, no leakage
- Compact structure, high pressure,
- Pulsation free flow & Low noise
- Strong self-priming ability
- FDA standards to ensure food safety
- Stepless-adjustment flow
- Suitable for -0.1 Mpa~2Mpa closed systems, resistant to impact loads

Operating Conditions

- Altitude: ≤ 2500 M
- Humidity environment: $\leq 75\%$
- Fluid viscosity: 0 ~ 1000 CPS
- Ambient temperature: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$
- Fluid temperature: $-10^{\circ}\text{C} \leq T \leq 100^{\circ}\text{C}$ (customized)
- Working way: continuous working
- Liquid type: water, antifreeze, acid and alkali, organic solvents, oils.
- Lifetime: 8000 hours

Order Code

MG 2 04 X K / DC 24 WI

Series
2/3: 2 series or 3 series

Gear height
04: 4mm
09: 9mm
13: 13mm

Pump housing
X: stainless steel
P: PPS
Y: hardened stainless steel

Gear material
K: PEEK
T: Hastelloy

Voltage
DC: direct current
AC: alternating current

Voltage
12: 12VDC
24: 24VDC
220: 220VAC
380: 380VAC

Motor
WI: brushless + built-in controller
W: brushless + external controller
No mark: brushed motor
B: stepper motor

Specification





Item Number	Max Pressure (Bar)	Max Flow rate (ml/Min)	Power (W)	Voltage (VDC)	Inlet/Outlet Diameter	ml/rpm (reference 3500RPM)
MG204XK/DC24WI	10	20-1000	70	24	G1/8"	0.27
MG209XK/DC24WI	7	100-2500	70	24	G1/8"	0.5
MG213XK/DC24WI	7	300-3500	70	24	G1/8"	0.75

Note: 1. Gear type: "XK" for common fluid, "YT" for fluid with rigid particles, "PK" for acid and alkali
2. Valve: "L" limited pressure valve, "R" non return valve
3. Voltage: 12V DC optional
4. Inlet/Outlet type: G1/4" or NPT1/8" optional
5. High temperature fluid: "H" for 50-100°C

MG200 Series

Brushless Magnetic Driving Gear Pump

Curve



Note: 1. Usually suggested to work under 3500RPM, not higher than this. 2. Above test result basis on the medium of water

Dimension (mm)

